WPF6 Probe
100 kHz - 6 GHz


- **High sensitivity from 0.2 V/m**
- **Isotropic & True RMS measurement**
- **Excellent attenuation at 50/60 Hz**
- **Measurements in accordance with International Standards**

100 kHz - 6 GHz

E

RMS

ISOTROPIC



Telecommunications
Certification and audit of telecommunication services (GSM, 3G, LTE, TDT, FM, WiFi, etc.).

Industry
Assessment of industrial processes for worker's exposure protection

Radar/Aerospace
Assessment of radar and aerospace sites and personnel exposure protection.

Labs/R&D
RF exposure protection of R&D and labs personnel.



Technical Specifications

	WPF6	WPF6-HP High Power version
Part Number	WWP0601	WWP0602
Frequency range	100 kHz – 6 GHz	
Sensor type	Isotropic RMS diode technology	
Type of frequency response	Flat	
Measurement range	0.2 – 130 V/m (CW) 0.2 – 20 V/m (True RMS)	0.2 – 1000 V/m (CW) 0.2 – 20 V/m (True RMS)
Dynamic range	56 dB	73 dB
Sensitivity	0.2 V/m	
Resolution	0.02 V/m (until 7.5 V/m) 0.1 V/m (from 7.5 V/m to 130 V/m)	
Frequency response (*)	Better than -3 dB @ 100 kHz ± 1.5 dB (250 kHz – 5.5 GHz) Better than -2 dB (5.5 – 6 GHz)	
Linearity	± 0.5 dB (0.5 V/m – 100 V/m)	
Isotropic deviation	± 0.3 dB (1 GHz) ± 1 dB (6 GHz)	
Calibration	ISO 17025 Accredited Calibration (ILAC)	
Calibration period	24 months (recommended)	
Temperature range	- 20 ºC to 50 ºC	
Temperature response	+ 0.1 / - 1 dB (related to 20 ºC)	
Dimensions	28.4 cm x 6 cm Ø	
Weight	95 g	
Attenuation at 50/60 Hz	> 55 dB	

(*) The frequency response can be corrected with the SMP3/SMP2 by using the correction factors stored in the probe (ISO 17025 accredited calibration).



Compatible with SMP3, SMP2, MonitEM, MapEM

WPF6_EN_2607_v2.7

WAVECONTROL
Safety, Quality, Service

Wavecontrol S.L.
Barcelona, Spain
+34 933 208 055
info@wavecontrol.com

Wavecontrol Inc.
New Jersey, USA
+1 201 479 9022
sales@wavecontrol.com

Product specifications and descriptions in this document subject to change without notice